

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** APP 1K-Kunststoffprimer-Spray APP Nr. 020905
- **Application of the substance / the preparation** Priming
Intended use: One-component ground-coat for plastics in spray 400ml
- **Manufacturer/Supplier:**
APP Auto-Plast Produkt Sp.z o.o
ul. Przemyslowa 10
PL- 62-300 Wrzesnia
Tel.: +48 (0)61 437 00 00
Fax: +48 (0)61 437 91 37
e-mail: app@app.com.pl
www.app.com.pl
- **Further information obtainable from:** Laboratory
- **Information in case of emergency:** +48 (0)61 437 00 00

2 Hazards identification

- **Hazard description:**



Xn Harmful
F+ Extremely flammable

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Warning! Pressurized container.

Has a narcotizing effect.

R 12 Extremely flammable.

R 36/38 Irritating to eyes and skin.

R 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.

R 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 63 Possible risk of harm to the unborn child.

R 67 Vapours may cause drowsiness and dizziness.

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**








- **Description:** Mixture of substances listed below with nonhazardous additions.

- **Dangerous components:**

CAS: 67-64-1 EINECS: 200-662-2	acetone Xn Xi, F; R 11-36-66-67	25-50%
CAS: 108-88-3 EINECS: 203-625-9	toluene Repr. Cat. 3; Xn Xi, F; R 11-38-48/20-63-65-67	25-50%

(Contd. on page 2)

Trade name: APP 1K-Kunststoffprimer-Spray

		(Contd. of page 1)
CAS: 106-97-8 EINECS: 203-448-7	butane  F+; R 12	12,5-20%
CAS: 74-98-6 EINECS: 200-827-9	propane  F+; R 12	2.5-10%
CAS: 64742-95-6 EINECS: 265-199-0	Solvent naphtha (petroleum), light arom.  Xn,  Xi,  N; R 10-37-51/53-65-66-67	2.5-10%
CAS: 108-90-7 EINECS: 203-628-5	chlorobenzene  Xn,  N; R 10-20-51/53	<1%

· **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:**
Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.
- **After swallowing:** If symptoms persist consult doctor.

5 Fire-fighting measures

- **Suitable extinguishing agents:** CO₂, sand, extinguishing powder. Do not use water.
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:**
Wear self-contained respiratory protective device.
Do not inhale explosion gases or combustion gases.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
Inform respective authorities in case of seepage into water course or sewage system.
Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
Dispose contaminated material as waste according to item 13.
Ensure adequate ventilation.
Do not flush with water or aqueous cleansing agents

7 Handling and storage

- **Handling:**
- **Information for safe handling:**
Ensure good ventilation/exhaustion at the workplace.
Open and handle receptacle with care.
- **Information about fire - and explosion protection:**
Do not spray onto a naked flame or any incandescent material.
Keep ignition sources away - Do not smoke.
Protect against electrostatic charges.
Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C, i.e. electric lights. Do not pierce or burn, even after use.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:**
Store in a cool location.
Observe official regulations on storing packagings with pressurized containers.

(Contd. on page 3)

Trade name: APP 1K-Kunststoffprimer-Spray

(Contd. of page 2)

- **Information about storage in one common storage facility:** Store away from foodstuffs.
- **Further information about storage conditions:**
 - Keep container tightly sealed.
 - Do not seal receptacle gas tight.
 - Store in cool, dry conditions in well sealed receptacles.
 - Protect from heat and direct sunlight.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

67-64-1 acetone

WEL Short-term value: 3620 mg/m³, 1500 ppm
Long-term value: 1210 mg/m³, 500 ppm

108-88-3 toluene

WEL Short-term value: 574 mg/m³, 150 ppm
Long-term value: 191 mg/m³, 50 ppm
Sk

106-97-8 butane

WEL Short-term value: 1810 mg/m³, 750 ppm
Long-term value: 1450 mg/m³, 600 ppm
Carc (if more than 0.1% of buta-1.3-diene)

- **Additional information:** The lists valid during the making were used as basis.

- **Personal protective equipment:**

- **General protective and hygienic measures:**

Keep away from foodstuffs, beverages and feed.
Immediately remove all soiled and contaminated clothing
Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the eyes and skin.

- **Respiratory protection:**

In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.

- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

(Contd. on page 4)

Trade name: APP 1K-Kunststoffprimer-Spray

(Contd. of page 3)

· **Eye protection:**



Tightly sealed goggles

9 Physical and chemical properties

· **General Information**

Form: Aerosol
Colour: According to product specification
Odour: Characteristic

· **Change in condition**

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: -44°C

· **Flash point:** < 0°C (DIN 53213)

· **Ignition temperature:** 365.0°C (DIN 51794)

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· **Explosion limits:**

Lower: 1.2 Vol %
Upper: 13.0 Vol %

· **Vapour pressure at 20°C:** 8300.0 hPa

· **Density at 20°C:** 0.764 g/cm³ (DIN 53217)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Solvent separation test:** < 3 %

· **Solvent content:**

Organic solvents: 98.4 %
VOC (EC) 752.0 g/l

· **Solids content (weight-%):** 1.4 %

10 Stability and reactivity

· **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

108-88-3 toluene

Oral	LD50	5000 mg/kg (rat)
Dermal	LD50	12124 mg/kg (rabbit)
Inhalative	LC50/4 h	5320 mg/l (mouse)

(Contd. on page 5)

Trade name: APP 1K-Kunststoffprimer-Spray

(Contd. of page 4)

64742-95-6 Solvent naphtha (petroleum), light arom.

Oral	LD50	>6800 mg/kg (rat)
Dermal	LD50	>3400 mg/kg (rab)
Inhalative	LC50/4 h	>10.2 mg/l (rat)

· **Primary irritant effect:**

· **on the skin:** Irritant to skin and mucous membranes.

· **on the eye:** Irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Harmful to fish

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Harmful to aquatic organisms

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 01 11	waste paint and varnish containing organic solvents or other dangerous substances
14 06 03	other solvents and solvent mixtures
15 01 04	metallic packaging

· **Uncleaned packaging:**

· **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

· **Land transport ADR/RID (cross-border)**



· **ADR/RID class:** 2 5F Gases.

· **Danger code (Kemler):** 23

· **UN-Number:** 1950

· **Packaging group:** -

· **Hazard label:** 2.1

(Contd. on page 6)

Trade name: APP 1K-Kunststoffprimer-Spray

(Contd. of page 5)

· **Description of goods:** 1950 AEROSOLS

· **Maritime transport IMDG:**



· **IMDG Class:** 2.1
 · **UN Number:** 1950
 · **Label** 2.1
 · **Packaging group:** -
 · **EMS Number:** F-D,S-U
 · **Marine pollutant:** No
 · **Proper shipping name:** AEROSOLS

· **Air transport ICAO-TI and IATA-DGR:**



· **ICAO/IATA Class:** 2.1
 · **UN/ID Number:** 1950
 · **Label** 2.1
 · **Packaging group:** -
 · **Proper shipping name:** AEROSOLS, flammable

15 Regulatory information

· **Labelling according to EU guidelines:**

The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

· **Code letter and hazard designation of product:**

Xn Harmful
 F+ Extremely flammable

· **Hazard-determining components of labelling:**

Toluene, Solvent naphtha

· **Risk phrases:**

36/38 Irritating to eyes and skin.
 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
 52/53 Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
 63 Possible risk of harm to the unborn child.
 66 Repeated exposure may cause skin dryness or cracking.
 67 Vapours may cause drowsiness and dizziness.

· **Safety phrases:**

1/2 Keep locked up and out of reach of children
 24/25 Avoid eyes and skin contamination
 36/37 Wear suitable protective clothing and Glover.
 45 In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible)
 51 Use only in well-ventilated areas.
 61 Avoid release to the environment. Refer to special instructions/ material safety data sheet

(Contd. on page 7)

GB

Trade name: APP 1K-Kunststoffprimer-Spray

(Contd. of page 6)

· Special labelling of certain preparations:

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50°C. Do not pierce or burn, even after use.

Do not spray on a naked flame or any incandescent material. Keep away from sources of ignition - No smoking.

Buildup of explosive mixtures possible without sufficient ventilation.

Keep out of the reach of children

· National regulations:

· Information about limitation of use:

None of the ingredients is listed.

Class	Share in %
NK	50-100

Valid regulations:

- Decree of European Council no. 1907/2006 from 16.12.2006 regarding registering, evaluation, certification and authorizations in range of chemicals (REACH), creation of European Chemicals Agency, changing Directive 1999/45/EC and cancelling decree of Council no. 793/93 and decree of Commission no.1488/94, as well as directives 76/769/EC, 91/155/EC, 93/67/EC, 93/105/EC and 2000/21/EC (30.12.2006 PL Official Journal of European Union L 396/1)
- Act from 11.01.2001 regarding chemical substances and products (Journal of Laws No. 11 pos. 84 from 2001) with later changes.
- Act from 27.04.2001 regarding wastes (Journal of Laws No.62 pos. 628 from 2001) with decree of Minister of Environment (Journal of Laws No. 152 pos. 1735 – 1737 from 2001)
- Act from 11.05.2001 regarding packages and packing materials (Journal of Laws No. 63 pos. 638 from 2001) with later changes.
- Announcement of Polish Parliament Marshal from 04.07.2006 regarding announcement of uniform act text – Environment protection law (Journal of Laws No. 129 pos. 902 from 2006)
- Act from 28.10.2002 regarding road transport of dangerous products (Journal of Laws No. 199 pos. 1671 from 2002) with later changes.
- Decree of Minister of Health from 30.04.2004 regarding dangerous substances and products, which packages must be equipped with closures, impeding opening by children and equipped with danger warning (Journal of Laws No. 128 pos. 1348 from 2004)
- Decree of Minister of Health from 02.09.2003 regarding marking of packages of dangerous substances and products (Journal of Laws No. 173 pos. 1679 from 2003) with change from 09.11.2004. (Journal of Laws No. 260 from 2004) with giving consideration to Directive 2006/8/EC from 23.01.2006
- Decree of Minister of Health from 02.09.2003 regarding criteria and classification method of chemical substances and products (Journal of Laws No. 171 pos. 1666 from 2003) with change from 04.11.2007. (Journal of Laws No. 174 pos. 1222)
- Decree of Minister of Health from 13.11.2007 regarding characteristics card (Journal of Laws No. 215 pos. 1588 from 2007)
- Decree of Minister of Health from 28.09.2005 regarding list of dangerous substances with classification and marking (Journal of Laws No. 201 pos. 1674 from 2005)
- Decree of Minister of Labour and Social Policy from 29.11.2002 regarding TLV of harmful factors in work environment (Journal of Laws No. 217 pos. 1833 from 2002) with change (Journal of Laws No. 217 pos. 1833 from 2005 and Journal of Laws No. 161 pos. 1142 from 2007)
- Government declaration from 26.07.2005 regarding coming into force changes to appendices A and B of European agreement, regarding international road transport of dangerous products (ADR), made out in Geneva in 30.09.1957 (Journal of Laws No. 178 pos. 1481 from 2005)
- Decree of Minister of Environment from 27.09.2001 regarding waste catalogue (Journal of Laws No. 112 pos. 11206 from 2001)
- Decree of Minister of Labour and Social Policy from 11.06.2002, changing the decree regarding general industrial safety regulations (Journal of Laws No. 91 pos. 811 from 2002)
- Decree of Minister of Economy from 09.06.2006, changing the decree regarding minimum requirements of industrial safety for employees in work stations, where explosive atmosphere may occur (Journal of Laws No. 121 pos. 836 from 2006)
- Decree of Government from 30.07.2002 changing the decree regarding list of works forbidden for women (Journal of Laws No. 127 pos. 1092 from 2002)
- Decree of Minister of Health from 20.04.2005 regarding tests and measurement of harmful factors in work environment (Journal of Laws No. 73 pos. 645 from 2005)
- Decree of Minister of Health and Social Security from 30.05.1996 regarding medical examinations of employees, prophylactic health care of employees and medical certificates, issued for purposes provided in labour code (Journal of Laws No. 69 pos. 332 from 1996) with later changes (Journal of Laws No. 37 pos. 451 and Journal of Laws No. 128 pos. 1405 from 2001)
- Decree of Government from 24.08.2004 regarding list of works forbidden for juvenile and conditions of their employing in some works (Journal of Laws No. 200 pos. 2047 from 2004) with later changes (Journal of Laws No. 136 pos. 1145 from 2005)
- Decree of Minister of Economy and Labour from 05.07.2004 regarding limitations, production prohibition or conditions, turnover or application of dangerous substances and products (Journal of Laws No. 168 pos. 1762 from 2004) with later changes (Journal of Laws No. 39 pos. 372 from 2005 and Journal of Laws No. 127 pos.887 from 2006)
- Decree of Minister of Health from 01.12.2004 regarding carcinogenic substances, products, factors or technological processes with carcinogenic or mutagenic influence in work environment (Journal of Laws No. 280 pos. 2771 from 2004) with later changes (Journal of Laws No. 160 pos. 1356 from 2005)
- Act from 29.07.2005 regarding drug addiction fight (Journal of Laws No. 179 pos. 1485 from 2005) with change (Journal of Laws No. 120 pos. 826 from 2006 and decree of European Parliament and Council from 11.02.2004 regarding drugs precursors (Official Journal EC L 047 from 18.02.2005) and decree of Council No. 111/2005 from 22.12.2004, defining rules of trade supervision of drugs precursors between Union and third countries (Official Journal EC L 22 from 16.01.2005, page 1; Official Journal EC Polish special edition from 2005, part 48, page 1).

Trade name: APP 1K-Kunststoffprimer-Spray

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

· **Relevant R-phrases**

- 10 Flammable.
- 11 Highly flammable.
- 12 Extremely flammable.
- 20 Harmful by inhalation.
- 36 Irritating to eyes.
- 37 Irritating to respiratory system.
- 38 Irritating to skin.
- 48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 63 Possible risk of harm to the unborn child.
- 65 Harmful: may cause lung damage if swallowed.
- 66 Repeated exposure may cause skin dryness or cracking.
- 67 Vapours may cause drowsiness and dizziness.

· **Department issuing MSDS:** APP Auto-Plast Produkt Sp.z o.o

· **Contact:** Rafal Roguszka

· *** Data compared to the previous version altered.**