

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

1 Identification of the substance/preparation and of the company/undertaking

- **Product details**
- **Trade name:** 050103 APP U 200 UBS
- **Article number:** 21-50310-0270
- **Application of the substance / the preparation** Surface protection
- **Manufacturer/Supplier:**
Auto-Plast Produkt Sp. z o.o.
ul. Przemysłowa 10
62-300 Września
tel.: +48 61 437 00 12
fax: +48 61 437 91 37
www.app.com.pl
Poland
- **Further information obtainable from:** r.roguszka@app.com.pl
- **Information in case of emergency:**
During normal opening times:
+48 61 4370012

2 Hazards identification

- **Hazard description:**



Xi Irritant
F Highly flammable
N Dangerous for the environment

- **Information concerning particular hazards for human and environment:**

The product has to be labelled due to the calculation procedure of the "General Classification guideline for preparations of the EU" in the latest valid version.

Has a narcotizing effect.

R 11 Highly flammable.

R 38 Irritating to skin.

R 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

R 67 Vapours may cause drowsiness and dizziness.

- **Classification system:**

The classification is according to the latest editions of the EU-lists, and extended by company and literature data.

3 Composition/information on ingredients

- **Chemical characterization**
- **Description:** Mixture of synthetic rubber, resins, fillers and solvents

- **Dangerous components:**

CAS: 64742-49-0 EINECS: 265-151-9	Naphtha (petroleum), hydrotreated light	Xn, Xi, F, N; R 11-38-51/53-65-67	25-50%
CAS: 1330-20-7 EINECS: 215-535-7	xylene (mix)	Xn, Xi; R 10-20/21-38	2.5-10%
CAS: 67-56-1 EINECS: 200-659-6	methanol	T, F; R 11-23/24/25-39/23/24/25	0.1-1.0%

- **Additional information:** For the wording of the listed risk phrases refer to section 16.

4 First-aid measures

- **After inhalation:** In case of unconsciousness place patient stably in side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.

(Contd. on page 2)

GB

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

Trade name: 050103 APP U 200 UBS

(Contd. of page 1)

- **After eye contact:** Rinse opened eye for several minutes under running water.
- **After swallowing:** Do not induce vomiting; call for medical help immediately.

5 Fire-fighting measures

- **Suitable extinguishing agents:**
 - Water haze
 - Fire-extinguishing powder
 - Carbon dioxide
 - Alcohol resistant foam
- **For safety reasons unsuitable extinguishing agents:** Water with full jet
- **Protective equipment:** Mount respiratory protective device.

6 Accidental release measures

- **Person-related safety precautions:** Wear protective equipment. Keep unprotected persons away.
- **Measures for environmental protection:**
 - Do not allow product to reach sewage system or any water course.
 - Prevent seepage into sewage system, workpits and cellars.
 - Inform respective authorities in case of seepage into water course or sewage system.
 - Do not allow to enter sewers/ surface or ground water.
- **Measures for cleaning/collecting:**
 - Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).
 - Ensure adequate ventilation.

7 Handling and storage

- **Handling:**
- **Information for safe handling:** Ensure good ventilation/exhaustion at the workplace.
- **Information about fire - and explosion protection:**
 - Keep ignition sources away - Do not smoke.
 - Protect against electrostatic charges.
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** Store in a cool location.
- **Information about storage in one common storage facility:**
 - Observe official regulations on storing packagings with pressurized containers.
- **Further information about storage conditions:**
 - Keep receptacle tightly sealed.
 - Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls/personal protection

- **Additional information about design of technical facilities:** No further data; see item 7.

- **Ingredients with limit values that require monitoring at the workplace:**

1330-20-7 xylene (mix)

WEL	Short-term value: 441 mg/m ³ , 100 ppm Long-term value: 220 mg/m ³ , 50 ppm Sk; BMGV
-----	--

67-56-1 methanol

WEL	Short-term value: 333 mg/m ³ , 250 ppm Long-term value: 266 mg/m ³ , 200 ppm Sk
-----	---

- **Additional information:** The lists valid during the making were used as basis.

(Contd. on page 3)

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

Trade name: 050103 APP U 200 UBS

(Contd. of page 2)

- **Personal protective equipment:**
- **General protective and hygienic measures:** Keep away from foodstuffs, beverages and feed. Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.
Do not inhale gases / fumes / aerosols.
Avoid contact with the skin.
Avoid contact with the eyes and skin.
- **Respiratory protection:**
In case of brief exposure or low pollution use respiratory filter device. In case of intensive or longer exposure use self-contained respiratory protective device.
Filter A
- **Protection of hands:**



Protective gloves

Solvent resistant gloves
Selection of the glove material on consideration of the penetration times, rates of diffusion and the degradation

- **Material of gloves** Nitrile rubber, NBR
- **Penetration time of glove material**
The exact break trough time has to be found out by the manufacturer of the protective gloves and has to be observed.
- **Eye protection:**



Tightly sealed goggles

- **Body protection:** Use protective suit.

9 Physical and chemical properties

· General Information

Form:	Fluid
Colour:	According to product specification
Odour:	Characteristic

· Change in condition

Melting point/Melting range: Undetermined.
Boiling point/Boiling range: 78°C

· **Flash point:** -9°C

· **Ignition temperature:** 200.0°C

· **Self-igniting:** Product is not selfigniting.

· **Danger of explosion:** Product is not explosive. However, formation of explosive air/vapour mixtures are possible.

· Explosion limits:

Lower:	0.8 Vol %
Upper:	7.7 Vol %

· **Vapour pressure at 20°C:** 4 Bar

· **Density at 20°C:** 1.04000 g/cm³

(Contd. on page 4)

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

Trade name: 050103 APP U 200 UBS

(Contd. of page 3)

· **Solubility in / Miscibility with water:** Not miscible or difficult to mix.

· **Solvent content:**
Organic solvents: 50.5 %

10 Stability and reactivity

- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Dangerous reactions** No dangerous reactions known.
- **Dangerous decomposition products:** No dangerous decomposition products known.

11 Toxicological information

· **Acute toxicity:**

· **LD/LC50 values relevant for classification:**

1330-20-7 xylene (mix)

Oral	LD50	8700 mg/kg (rat)
Dermal	LD50	2000 mg/kg (rbt)
Inhalative	LC50/4 h	6350 mg/l (rat)

· **Primary irritant effect:**

- **on the skin:** Irritant to skin and mucous membranes.
- **on the eye:** No irritating effect.

· **Sensitization:** No sensitizing effects known.

· **Additional toxicological information:**

The product shows the following dangers according to the calculation method of the General EU Classification Guidelines for Preparations as issued in the latest version:

Irritant

12 Ecological information

· **Ecotoxicological effects:**

· **Remark:** Toxic for fish

· **General notes:**

Water hazard class 2 (German Regulation) (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Danger to drinking water if even small quantities leak into the ground.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

· **Product:**

· **Recommendation**

Must not be disposed together with household garbage. Do not allow product to reach sewage system.

· **European waste catalogue**

08 02 99	wastes not otherwise specified
20 01 27	paint, inks, adhesives and resins containing dangerous substances

(Contd. on page 5)

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

Trade name: 050103 APP U 200 UBS

(Contd. of page 4)

- **Uncleaned packaging:**
- **Recommendation:** Disposal must be made according to official regulations.

14 Transport information

- **Land transport ADR/RID (cross-border)**
- **ADR/RID class:** 3 Flammable liquids.
- **Danger code (Kemler):** 33
- **UN-Number:** 1139
- **Packaging group:** II
- **Hazard label** 3
- **Description of goods:** 1139 COATING SOLUTION, special provision 640D
- **Limited quantities (LQ)** LQ6

- **Maritime transport IMDG:**
- **IMDG Class:** 3
- **UN Number:** 1139
- **Label** 3
- **Packaging group:** II
- **EMS Number:** F-E,S-E
- **Marine pollutant:** No
- **Proper shipping name:** COATING SOLUTION

- **Air transport ICAO-TI and IATA-DGR:**
- **ICAO/IATA Class:** 3
- **UN/ID Number:** 1139
- **Label** 3
- **Packaging group:** II
- **Proper shipping name:** COATING SOLUTION

15 Regulatory information

- **Labelling according to EU guidelines:**
The product has been classified and marked in accordance with EU Directives / Ordinance on Hazardous Materials.

- **Code letter and hazard designation of product:**



Xi Irritant
F Highly flammable
N Dangerous for the environment

- **Risk phrases:**

11 Highly flammable.
38 Irritating to skin.
51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
67 Vapours may cause drowsiness and dizziness.

- **Safety phrases:**

2 Keep out of the reach of children.
9 Keep container in a well-ventilated place.
16 Do not store in the ignition sources vicinity – do not smoke
23 Do not breathe fumes.
29/56 Do not empty into drains, dispose of this material and its container at hazardous or special waste collection point.
46 If swallowed, seek medical advice immediately and show this container or label.
51 Use only in well-ventilated areas.

(Contd. on page 6)

Safety Data Sheet

According to 1907/2006 EEC (REACH), Article 31

Printing date 22.08.2007

Revision: 29.03.2007

Trade name: 050103 APP U 200 UBS

(Contd. of page 5)

- **National regulations:**

- **Technical instructions (air):**

Class	Share in %
I	0,1-1,0
NK	25-50

- **Waterhazard class:** Water hazard class 2 (Self-assessment): hazardous for water.
- **VOC-CH** 50.46 %
- **VOC-EU** 524.7 g/l
- **Danish MAL Code** 5-3

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- **Relevant R-phrases**

- 10 Flammable.
- 11 Highly flammable.
- 20/21 Harmful by inhalation and in contact with skin.
- 23/24/25 Toxic by inhalation, in contact with skin and if swallowed.
- 38 Irritating to skin.
- 39/23/24/25 Toxic: danger of very serious irreversible effects through inhalation, in contact with skin and if swallowed.
- 51/53 Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.
- 65 Harmful: may cause lung damage if swallowed.
- 67 Vapours may cause drowsiness and dizziness.

- **Department issuing MSDS:** Research & Development

- **Contact:** Rafał Roguszka