

SPECIFICATIONS

Prepared on:
July 18, 2007




Updated on:
July 18, 2007

Page 1 of 2

Product name: SALON Cleaner

Preparation for corrections of preservative layer defects.

<u>Container:</u>	1.0 l; 10 l
<u>Basic components:</u>	Hydrogen-treated low-boiling oil fraction, amphoteric surface-active agent
<u>pH:</u>	7 – 8
<u>Colour:</u>	White
<u>Density:</u>	0.94 g/cm ³ (at the temperature of 20 °C)
<u>Smell:</u>	Characteristic
<u>Usage:</u>	An agent intended for the quick and efficient removal of grease, oil and paraffin wax, which provides cleaned surfaces with a glossy appearance. In particular, it is recommended for making corrections if the original preservative layer in a new car is lost or defected.



<u>Directions for use:</u>	Remove dirt immediately after having sprayed the preparation onto the cleaned surface - wipe it with a sponge or microfibre cloth. Polish the surface with a clean and dry cloth to obtain a high gloss.
----------------------------	--



<u>Constraints:</u>	The product does not have additives allowing for long-term protection.
<u>Equipment cleaning:</u>	Inorganic solvents.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**

SPECIFICATIONS

Prepared on:
July 18, 2007




Updated on:
July 18, 2007

Page 2 of 2

Product name: SALON Cleaner

Storage:



Store in original, closed containers in a dry and well-ventilated room.
Protect against freezing.

Industrial safety regulations:



For professional use only.
See: information on product labels and/or in Hazardous Material Safety Data Sheet.
Users should observe all industrial safety regulations applicable in their countries.

Hazards:



See Material Safety Data Sheet

- the product is harmful
- the product may cause lung damage if swallowed
- repeated exposure may cause dry and cracked skin
- product vapours may cause drowsiness and dizziness
- 5-chloro-2-methyl-(2H)-isothiazoline-3-one and 2-methyl-(2H)-isothiazoline-3-one contained in the product may cause sensitisation

R65 Harmful: May cause lung damage if swallowed.
R66 Repeated exposure may cause dry and cracked skin.
R67 Vapours may cause drowsiness and dizziness.
S2 Keep out of the reach of children.
S23 Do not breathe vapour and sprayed liquid.
S24/25 Avoid contact with skin and eyes.
S45 In case of accident or if you feel unwell, seek medical advice immediately (show the label whenever possible.).
S62 If swallowed, do not induce vomiting; seek medical advice immediately and show this container or label.

The above information complies with the current knowledge on our products and their possible applications. This guarantees no specific properties or usability in particular conditions. Users should observe guidelines and warnings provided on product labels and specified in material safety data sheets. We hold no responsibility if conditions beyond our control affect the final result of work.

**Auto Plast Produkt Sp. z o.o. [Ltd.] 62-300 Września, ul. Przemysłowa 10, Poland
tel. + 48(prf)61 437 00 00**